

## Top Tec 6200 0W-20



### Description

High-tech low-friction motor oil based on synthetic technology. Developed for the high requirements of Audi, Porsche, Seat, Škoda and VW. The lower viscosity of the Longlife IV lubricant ensures excellent cold-start behavior and improves the engine efficiency. Offers an additional reduction of approx. 1.5 % in consumption compared with the already fuel-saving Longlife III. Innovative additive technology guarantees excellent protection against wear, impressive engine cleanliness and greater oxidation stability. Enables extremely long oil change intervals (WIV etc.).

### Properties

- excellent cold-start behavior
- excellent wear resistance
- highest fuel economy
- shortens the start time
- outstanding resistance to oxidation
- optimum protection when using E10 fuel
- increases operational reliability
- tested for turbochargers and catalytic converters

### Specifications and approvals:

VW 508 00 • VW 509 00

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

ACEA C5 • Porsche C20

### Technical data

Viscosity SAE class	0W-20 SAE J300
Density at 15 °C	0,835 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	39,6 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35°C (CCS)	<= 6200 mPas ASTM D 5293
Viscosity index	184 DIN ISO 2909
HTHS at 150°C	>= 2,6 mPas ASTM D 5481
Pour point	-60 °C DIN ISO 3016

### Technical data

Evaporation loss (Noack)	10,3 % CEC-L-40-A-93
Total base number	8,1 mg KOH/g DIN ISO 3771
Flash point	230 °C DIN ISO 2592
Sulfate ash	<= 0,8 % DIN 51575
Color / appearance	grün

### Areas of application

For various vehicles from Audi, Porsche, Seat, Škoda and VW. Use only in gasoline and diesel engines with a particulate filter (e.g. TSI, TFSI, TDI) that require a lubricant of VW standard 508 00/509 00 or Porsche standard C20. Tested for use with turbochargers and catalytic converters. Not backwards compatible.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed!

### Available pack sizes

1 l Canister plastic	20787 BOOKLET
4 l Canister plastic	20788 BOOKLET
5 l Canister plastic	20789 BOOKLET
20 l Canister plastic	20782 D-GB-I-E-P
60 l Drum sheet metal	20783 D-GB
205 l Drum sheet metal	20785 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**