

Chain lubrication oil for forklift trucks

Description

High-quality, thermostable, adherent and synthetic lubricant compound. With selected white solid lubricants that provide additional lubrication properties and show where the product has been applied. Suitable for all types of chains. Reduces chain elongation thanks to high pressure absorption capacity.

Properties

- excellent creep properties
- especially cold, hot and splash-water resistant
- high pressure-absorption capability
- optimum effectiveness when the product is used unmixed
- reduces chain elongation
- reduces friction and prevents stick slip
- outstanding corrosion protection
- excellent adhesion

Technical data

| | |
|--|---|
| Base | Syntheseöl, Polymergemisch / synthetic oil, mixed polymers |
| Color / appearance | hellgelb / pale yellow |
| Operating temperature range | -30 bis / to +180, kurzfristig bis / intermittent to +200 °C |
| Propellant | Propan, Butan / propane, butane |
| Shelf life in original sealed container | 60 months |

Areas of application

For initial and maintenance lubrication of power-transmission chains. Especially suitable for dusty, dirty and corrosive environments. Ideal for high-load chains thanks to extremely good adherence.

Application

Carefully clean chain with solvent. Then spray with the chain lubrication oil. The lubricant attains its final consistency and adherence once the solvent has evaporated.



Available pack sizes

| | |
|--------------------|---------------------|
| 400 ml Can aerosol | 20946 D-GB-I-E-P |
| 400 ml Can aerosol | 2282 D-RUS-UA |

Our information is based on thorough research and may be considered reliable, although not legally binding.