Product information

DPF/GPF Cleaner

PI 6/01/28/2025



Description

Non-flammable, ash-free cleaner for dissolving soot in exhaust particulate filters of gasoline and diesel engines. Used for restoring the absorption capacity of the particulate filter and can be applied during service without removal of the particulate filter.

Properties

- Application without removal of the diesel particulate filter
- Improves the load condition of the diesel particulate filter
- Allows forced regeneration after clogging
- Dissolves soot deposits
- Non-flammable
- Ash-free formula
- Residue-free evaporation

Technical data

Base special aqueous active ingredient

solution

Color/ aqueous, low-viscosity liquid

appearance

Form aerosol

Areas of application

Cleaning fluid for restoring the absorption capacity of the diesel particulate filter. To be applied in the event of indications of a heavily laden particulate filter, such as loss of performance or increased fuel consumption. For preventative use with an unfavorable driving profile.

Application

Remove the temperature or pressure sensor at the diesel particulate filter. In intervals, spray the cleaner through the resulting opening in the direction of the particulate filter (hold can vertically). Then refit the sensors and carry out regeneration according to the manufacturer's instructions. Clear any existing error codes. Application only by professional workshops and specialists! Attention: Notes from the vehicle manufacturer must be strictly observed!

Available pack sizes

400 ml Can aerosol 21942

D-GB-NL-F

400 ml Can aerosol 21969

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.



Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de