

Coolant & Antifreeze KFS P-OAT GE

Description

Innovative combination of active agents with phosphate inhibitor package based on hybrid technology (P-OAT). Offers the engine optimum protection against frost, corrosion, and overheating across the entire service life. Amine-, borate-, silicate-, and nitrite-free radiator antifreeze based on ethylene glycol. Can be used without limitations in engines made of cast iron, aluminum or a combination of the two and in cooling systems made of aluminum or copper alloys.



ethylene glycol.

Properties

- Contains no amines, borates, silicates or nitrites
- outstanding corrosion protection
- provides outstanding protection against overheating
- prevents the cooling system from freezing up
- Excellent cavitation protection

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

ASTM D3306-20 • ASTM D6210-17 • Ford WSS-M97 B57-A1 • GB 29743-2013 • GB 27943-2022 • JIS K2234:2018 • KS M 2142:2014 • UNE 26-361-88/1

Technical data

Color / appearance	yellow
Density at 20 °C	1,119 g/cm ³
Recommended storage temperature	-20 - +35 °C
Shelf life in original sealed container	36 months
Base	concentrate

Areas of application

For all cooling systems and engines in passenger cars (combustion engines, hybrid and battery electric vehicles), commercial vehicles, motorcycles, buses, agricultural and construction machinery as well as stationary engines and equipment that require cooling system protection of this quality.

Application

Clean the cooling system with LIQUI MOLY Radiator Cleaner (part no. 3320). Then empty this and rinse with plenty of water. Fill with Coolant & Antifreeze KFS P-OAT GE and water according to the mixing table and the manufacturer's instructions. We recommend distilled water for this. Depending on water hardness and quality, dilution with tap water is also possible. Disposal according to the local regulations. Change interval according to manufacturer's instructions. Store undiluted only. Miscible with coolants based on

MIXING TABLE

Frost protection	Water	Protection up to
1 part	2 parts	-20 °C
1 part	1 part	-37 °C
2 parts	1 part	-69 °C

Available pack sizes

1 l Canister plastic	23139	DE-EN
5 l Canister plastic	23140	DE-EN-ES-IT-PT
20 l Canister plastic	23141	DE-EN-ES-IT-PT
60 l Black plate barrel	23142	DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.