Product information

PI 5/03/12/2026

Motorbike Gasoline System Cleaner



Description

Removes and prevents deposits on injectors, carburetors, intake valves, membranes, and piston skirts. Cleans spark plugs and the combustion chamber. Eliminates starting difficulties and rough engine idling. Protects the tank and fuel system from corrosion. Improves throttle response and overall drivability. Stabilizes fuel and protects against premature fuel aging. Optimizes emission levels (AU values) and engine performance. Clean engines use less fuel and reduce the pollutant emissions.

Properties

- removes deposits from injectors and carburetors
- cleans intake valves and the combustion chamber
- cleans the fuel system
- keeps the engine clean
- reduces pollutant emissions
- tested for the use with catalytic converters

Technical data

Odor	characteristic
Color / appearance	yellow
Form	liquid
Flash point	63 °C
Density	0,804 g/cm³

Areas of application

For all 2-stroke and 4-stroke motorcycle gasoline engines, gasoline fuels and operating conditions. For all types of mixture preparation (carburetors and fuel injectors). For preventive maintenance or to fix specific problems. To be added directly into the fuel tank. Safe for catalytic converters.

Application

For specific problems: Add 50 ml per 5 liters of fuel. Preventive maintenance: Add 25 ml per 5 liters of fuel. Can be mixed with fuel at any time, as it mixes automatically. If the problems reoccur, repeat the treatment.

Available pack sizes

250 ml Dispensing bottle plastic	23206 DE-EN-ES-IT-PT-FR-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com