Product information

PI 6/02/13/2026

Profi CV Gear Oil 75W-85



Description

Versatile gear oil with high performance reserves. Exceeds the high test requirements of well-known vehicle manufacturers. Ensures assemblies function perfectly, even under extreme operating conditions and when exposed to large temperature fluctuations. Offers high lubrication reliability and optimal wear protection. Reduces transmission noise and allows long oil change intervals.

Properties

- excellent viscosity/temperature properties
- outstanding seal compatibility
- excellent resistance to aging
- excellent wear resistance
- high pressure-absorption capability
- reduces gearshift resistance
- excellent corrosion protection
- reduces transmission noise

Specifications / Approvals

API GL5 • DTFR 12B120 • MB-Freigabe 235.33 • ZF TE-ML 12F

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Bosch TE-ML 08 • Detroit Diesel DFS 93K219.03 • MB 235.31 • SAE J 2360 • Scania STO 1:0 • ZF TE-ML 07A

Technical data

SAE class (gear oils)	75W-85 SAE J306
Density at 15 °C	0,855 g/cm³ DIN 51757
Viscosity at 40 °C	68,5 mm²/s ASTM D7042
Viscosity at 100 °C	11,7 mm²/s ASTM D7042
Viscosity at -40 °C (Brookfield)	⩽ 150000 mPas ASTM D2983
Viscosity index	165 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	185 °C DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

For use in high-load manual and differential transmissions, reduction gears, and mechanical steering systems in commercial vehicles, vans, off-road vehicles, and passenger cars.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

20 l Canister plastic	23210 DE-EN
60 l Black plate barrel	23211 DE-EN
205 l Black plate barrel	23212 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com