Product information

PI 6/02/18/2026

Top Tec Truck Gear 5150 75W-90



Description

High-performance gear oil with enormous performance reserves. Meets the high test requirements of well-known vehicle manufacturers. Ensures assemblies function perfectly, even under extreme operating conditions and when exposed to large temperature fluctuations. Offers high lubrication reliability and optimal wear protection. Reduces gearshift resistance and transmission noise. Enables very long oil change intervals.

Properties

- highest load-carrying capacity
- outstanding seal compatibility
- reduces transmission noise
- excellent viscosity/temperature properties
- excellent wear protection
- extremely long oil change intervals
- reduces gearshift resistance
- excellent corrosion protection

Specifications / Approvals

API GL4 • MAN 341 Typ GA2 • Scania STO 2:0 G

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm³ DIN 51757
Viscosity at 40 °C	105,0 mm²/s ASTM D7042
Viscosity at 100 °C	17,0 mm²/s ASTM D7042
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D2983
Viscosity index	180 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

For use in high-load manual transmissions in Scania series G, L, P, R, S, and T commercial vehicles as well as in Scania series K and N bus chassis. This lubricant is used on MAN commercial vehicles in TGS and TGX Euro 6 models with TipMatic (semi-automatic transmissions) 12+2 of types GRS and GZ (with and without retarder).

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

20 l Canister plastic	23213 DE-EN
60 l Black plate barrel	23214 DE-EN
205 l Black plate barrel	23251 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com