

Speed Tec Gasoline

Description

A state-of-the-art, ash-free fuel additive for improving combustion and acceleration in partial load range. Compatible with all gasoline and additive qualities. Improves considerably vehicle acceleration.

Properties

- improves the acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for catalytic converters
- does not influence the octane number
- better drivability

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / Additive mixture in carrier fluid
Color / appearance	hellbraun / light brown
Density at 15 °C	0,820 g/cm ³
Flash point	63 °C
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Used as an additive in the fuel of all 2-stroke and 4-stroke gasoline engines, especially for motor vehicle engines. Also can be used in two-wheeled vehicles. For the improvement of vehicle acceleration and smooth operation.

Application

One 250 ml can is sufficient for max. 70 liters of gasoline fuel. Mix the contents of the can with the gasoline fuel. Mixing also takes place automatically.



Available pack sizes

250 ml Can sheet metal	3720 D-GB-I-E-P
250 ml Can sheet metal	2788 GB-AUS
250 ml Can sheet metal	2848 GB-DK-FIN-N-S
250 ml Can sheet metal	3940 D-RUS-UA
250 ml Can sheet metal	20878 JP

Our information is based on thorough research and may be considered reliable, although not legally binding.