

A/C System Cleaner

Description

Cleaning fluid for removing mold and bacteria (e.g. legionella) simply and effectively from A/C systems in passenger cars, commercial vehicles, buses and in the home without dismantling. Leaves behind a pleasantly fresh fragrance after cleaning. **Use biocides safely. Always read the label and product information before use.**

Properties

- destroys molds and bacteria
- cleans air inlet ducts
- removes musty smells
- assures fresh, clean air
- forms a protective film
- increases ride comfort
- expert's microbiological report available

Technical data

Base	Desinfektionsmittel, Geruchshemmer, Duftstoffe / disinfectant, odour remover, fragrances
Color / appearance	farblos / colourless
Density at 20 °C	1,0 g/ml
Odor	Zitrone / lemon
Form	flüssig / liquid
Shelf life	24 Monate in original verschlossenen Gebinden / 24 months in original sealed containers
Solvent content	0 %
pH value	7
Shelf life in original sealed container	24 months

Areas of application

Used for cleaning and disinfecting air conditioning systems in passenger motor vehicles and commercial vehicles. The product can also be used for domestic air conditioning systems.

Application

Packed in portions:

1 l will treat one vehicle or one air conditioning system. If the manufacturer of the air conditioning system provides a cleaning service recommendation, this recommendation must be observed. If no model-specific instructions are available from the passenger car manufacturer, follow the LIQUI MOLY recommenda-



tion for application. If possible, spray the cleaning fluid directly onto the surface of the evaporator of commercial vehicle, bus and home A/C systems.

LIQUI MOLY recommended use:

- Keep the window open during the cleaning process. Avoid inhaling the vapors during cleaning.
- Check to make sure that the condensation water drainage openings are not blocked.
- Dry the surface of the evaporator for 10 minutes with the engine running using the following heater and blower settings: Switch off the air conditioning unit and set to air circulation. Set the air distribution switch to footwell. Turn the temperature regulator and blower selector to maximum.

Cleaning the air conditioning system:

- Insert the probe of the cleaner gun toward the evaporator (center of the vehicle) (see vehicle-specific instructions at www.liqui-moly.biz).
- Actuate the cleaner gun and move the spray probe carefully back and forth to flush out and clean the evaporator thoroughly.
- Allow 15 - 20 minutes for the cleaning fluid to take effect.
- Dry the surface of the evaporator for 10 minutes with the heater and blower at the same setting as prior to cleaning.
- Replace the dust and pollen filter.

Note: Any cleaner which is spilled must be wiped up using a damp cloth and water.

Available pack sizes

1 l Canister plastic	4091
	D-GB-F-I-E-P
5 l Canister plastic	4092
	D-GB-F-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.